

Stubby Ball End L-Wrenches





Up to 20% stronger, with more torque and twice the wear resistance of standard grades of steel.

FINISH OPTIONS:




Corrosion-resistant finish:

Environmentally safe, provides better tool grip, resists solvents and is 5 times more corrosion resistant than competitor finishes.

Traditional plated tool look with superior protection and durability.



Stubby L-Wrenches eliminate the need to trim and file the short arm. A trimmed L-Wrench introduces burrs, and still does not have the tight radius of a dedicated Stubby L-Wrench.



Stubby tools fit in tight spaces where there is not enough overhead clearance for a standard hex key.



Tighter inside radius means full smooth entry into screw head.

www.bondhus.com





Stubby Ball End L-Wrenches



	-7
rodra	10/
DRY SUPEACE	-
TERMIN OCY	

Corrosion-resistant finish:

Environmentally safe, provides better tool grip, resists solvents and is 5 times more corrosion resistant than competitor finishes.

PART#	MODEL#	PCS	LENGTH	CONTENTS	QTY
20599	SBLX22	22	Long	16537 (.050-3/8") + 16599 (1.5-10mm)	1



ProGuard[™]

Sets

Sets	PART#	MODEL#	PCS	LENGTH	CONTENTS	QTY
Inch	16538	SBLX10	10	Long	1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4"	1
	16537	SBLX13	13	Long	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8"	1
Metr	16592	SBLX7M	7	Long	1.5, 2, 2.5, 3, 4, 5, 6mm	1
men	16599	SBLX9M	9	Long	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm	1



BriteGuard. Next generation chrome finish:

Traditional plated tool look with superior protection and durability.

	Sets	PART#	MODEL#	PCS	LENGTH	CONTENTS	QTY
BriteGuard™ Sets	Inch	16738	SBLX10B	10	Long	1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4"	1
		16737	SBLX13B	13	Long	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8"	1
	Metric	16792	SBLX7MB	7	Extra Long	1.5, 2, 2.5, 3, 4, 5, 6mm	1
		16799	SBLX9MB	9	Extra Long	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm	1

Distributed by:

Bondhus Corporation

1400 E Broadway • PO Box 660 • Monticello, MN 55362 Tel: 763-295-2162 • Toll Free: 800-328-8310 • Fax: 763-295-4440